

HYDRAULIC BREAKER

Suitable excavators: 52911~132277 lbs



SPECIFICATION

Improved cushion damper to absorb repercussion from hammering and shaking absorption.
 High impact power.
 Less noise, less stress to hydraulic components as absorbing pressure fluctuation.

X-TERRA

BREAKER XTB SERIES


Model		XTB300	XTB360	XTB450	XTB550
Carrier	Lbs	52911-79366	61729-92594	74957-110231	88185-132277
Weight	Lbs	5291	5952	7275	8378
Accumulator Pressure	PSI	782	782	782	782
Operating Pressure	PSI	2276-2702	2276-2702	2276-2702	2276-2702
Required Oil Flow	GPM	47.55-63.40	52.83-68.68	58.12-73.97	63.40-84.54
Impact Rate (Long Stroke)	BPM	250-380	230-400	230-345	230-330
Impact Rate (Short Stroke)	BPM	300-450	270-470	270-410	270-550
Chisel Diameter	Inches	5.91	6.10	6.50	6.89
Relief Valve Setting Pressure	PSI	2987	3271	3271	2987

* The above specification may be changed without prior notice for product improvement.

Auto lubrication system (option)



Available tools



Scope of supply:

- breaker
- 2 chisels
- 2 hoses
- mounting cap
- tool kit
- manual