

HYDRAULIC BREAKER

Suitable excavators: 6614~27558 lbs



SPECIFICATION



Improved cushion damper to absorb repercussion from hammering and shaking absorption.
 High impact power.
 Less noise, less stress to hydraulic components as absorbing pressure fluctuation.

TERRA

BREAKER XTB SERIES


Model		XTB40	XTB60	XTB70	XTB80	XTB100
Carrier	Lbs	6614-14330	9921-17637	9921-17637	13228-22046	17637-27558
Weight	Lbs	573	728	1058	1202	1764
Accumulator Pressure	PSI	569	569	569	569	782
Operating Pressure	PSI	1565-2347	1707-2347	1991-2418	1991-2418	1991-2560
Required Oil Flow	GPM	9.25-18.49	10.57-29.06	11.89-26.42	13.21-26.42	19.81-31.70
Impact Rate (Long Stroke)	BPM	550-1300	380-1100	400-800	350-700	350-600
Impact Rate (Short Stroke)	BPM	-	-	600-1000	490-1000	600-900
Chisel Diameter	Inches	2.76	2.95	3.15	3.54	3.74
Relief Valve Setting Pressure	PSI	2489	2489	2489	2489	2987

* The above specification may be changed without prior notice for product improvement.

Auto lubrication system (option)



Available tools



Scope of supply:

- breaker
- 2 chisels
- 2 hoses
- mounting cap
- tool kit
- manual