

HYDRAULIC BREAKER

Suitable excavators: 22046~66139 lbs



SPECIFICATION



Improved cushion damper to absorb repercussion from hammering and shaking absorption.
 High impact power.
 Less noise, less stress to hydraulic components as absorbing pressure fluctuation.

TERRA

BREAKER XTB SERIES
 M


Model		XTB130	XTB150	XTB180	XTB200	XTB220	XTB250
Carrier	Lbs	22046-33069	26455-39683	35274-48502	39683-52911	44092-57320	48502-66139
Weight	Lbs	1984	2535	3197	3483	3968	4409
Accumulator Pressure	PSI	782	782	782	782	782	782
Operating Pressure	PSI	1991-2560	2276-2702	2276-2702	2276-2702	2276-2702	2276-2702
Required Oil Flow	GPM	21.13-36.98	21.13-36.98	26.42-40.95	31.70-44.91	31.70-50.19	39.63-55.48
Impact Rate (Long Stroke)	BPM	350-600	320-550	320-500	320-480	340-450	270-400
Impact Rate (Short Stroke)	BPM	600-900	400-700	400-650	400-600	420-550	330-500
Chisel Diameter	Inches	4.13	4.53	4.92	5.31	5.31	5.71
Relief Valve Setting Pressure	PSI	2987	2987	2987	2987	2987	2987

* The above specification may be changed without prior notice for product improvement.

Auto lubrication system (option)



Available tools



Scope of supply:

- breaker
- 2 chisels
- 2 hoses
- mounting cap
- tool kit
- manual